

Amendments to the Claims

This listing of claims will replace all prior versions, and listing, of claims in the application:

1-2. (Cancelled)

3. (Withdrawn) The system as claimed in claim 1, characterized in that the drive (2) is a fluidically acting drive device.

4. (Cancelled)

5. (Withdrawn) The system is claimed in Claim 1, characterized in that the load-bearing element (5) comprises a load-bearing parallelogram in which four sub-arms are connected to one another at joints with a horizontal pivot axis and in which the angle position and the lengths of the sub-arms of the load-bearing parallelogram located within the vertical plane is selectably changeable.

6-10. (Cancelled)

11. (Withdrawn) The system as claimed in claim 10, characterized in that the handling device (10) comprises at least two main parts (101, 102), of which the first part (101) is connected in a fixed manner, to the load-bearing element (5) and to the load-receiving device (7); and the second part (102), on which the manipulation force (F) acts, is

operative in response to the manipulation force to be moved relative to the first part (101); and the device (15) for generating the force-dependent signal (P) comprises at least one displacement sensor for sensing the change in position (AH) of the two parts (101, 102) relative to one another which occurs under the action of the manipulation force (F) .

12. (Cancelled)

13. (Withdrawn) The system as claimed in Claim 1, characterized by at least one fluidically acting brake (20) for the load-bearing element (5), having a cylinder-like housing (21), having a cover (22), which closes off the housing (21) on the top side, and a base plate (23), which closes off the housing (21) on the underside, and having a piston (24) which is guided such that it can be moved longitudinally in the housing (21) and subdivides the housing (21) into a sealed pressure chamber (25) for a pressure-generating fluid and into a spring chamber (26), the cover (22), base plate (23) and piston (24) each having a lead-through opening for the load-bearing element (5), there being arranged in the spring chamber (26), around the load-bearing element (5), at least two blocking elements (27) which are subjected to the action, on the one hand, of springs (28) and, on the other hand, of the piston (24) under the fluid-pressure action, the spring chamber (26) having a region (29) which tapers in the direction of the piston (24) such that the blocking elements (27), when they are located in a spring-side part of the region (29), in the presence of the fluid-pressure action, release the load-bearing element (5) and, when they are moved into a piston-side part of the region (29) under the action of the springs (28), in

the absence of the fluid-pressure action, arrest the load-bearing element (5) in the housing (21).

14. (Withdrawn) The system as claimed in claim 13, characterized in that the path-dependent signal (S), which corresponds to an essentially vertical (Z-Z) movement of the load-bearing element (5), serves as an input signal for controlling the brake (20), in particular for opening a pressure-relief valve for the pressure chamber (25).

15. (Withdrawn) The system as claimed in claim 13 or 14, characterized by two brakes (20) which are installed in positions rotated through 180° in relation to one another.

16. (Withdrawn) The system as claimed in one or more of claims 1 to 15, characterized by a safety controller for the drive (2) and/or for blocking the vertical (ZZ) movement of the load-bearing element (5), said controller having a sensor (18), in particular a light barrier, for registering the use of the handling device (10) and also having a switching member (19) which switches off the drive (2) and/or blocks the vertical (Z-Z) movement of the load-bearing element (5) and only switches on and/or releases the same (signal U) when the sensor (19) signals the use of the handling device (10) (signal A).

17. (Withdrawn) The system as claimed in Claim 10, characterized by a safety controller for a manually operable load-receiving mechanism of the load-receiving device (10), the safety controller having a safety control member (17) which is connected to the device (11) for generating the path-dependent signal (S) and the device (15) for

generating the force-dependent signal (P) and blocks the manual operation of the load-receiving mechanism and only releases it (signal B) when, in the presence of the force-dependent signal (P), there is no path-dependent signal (S) present.

18-21. (Cancelled)

22. (Withdrawn) The system as claimed in Claim 1, characterized by a crane trolley which is guided on a running-rail structure (4) in at least one horizontal (X-X) direction and which connects to the load-bearing element (5).

23. (Withdrawn) The system as claimed in Claim 22, characterized in that, for its movements in the horizontal direction (X-X and Y-Y), the load-lifting apparatus (1) is assigned at least one drive device which can be activated in dependence on a forced deflection of the load-bearing element (5), said deflection being based on the vertical alignment (Z-Z) which is established automatically as a result of gravitational force in the rest position.

24. (Withdrawn) A method of controlling a load-lifting apparatus (1), in particular by means of a system as claimed in one or more of claims 1 to 23, characterized in that, once a load (9) has been received, a force applied by a/the drive (2) or a corresponding torque is rapidly increased automatically until it corresponds to the weight of the load (9), it being the case that, in order to determine that a balanced state of the load (9), once

reached, has been set, a path-dependent signal (S) for an essentially vertical (Z-Z) movement of a/the load-bearing element (5) is determined.

25. (Withdrawn) The method as claimed in claim 24, characterized in that the path-dependent signal (S) is compared with a desired value (W) and, when the signal (S) and desired value (W) correspond ($\Delta S=0$), the force applied by the drive (2) or the torque is kept constant at the value reached.

26. (Withdrawn) The system as in Claim 2, wherein the electric motor is an electric servomotor.

27. (Withdrawn) A system for controlling a load lifting apparatus (1), comprising
a controllable drive (2);
a load-bearing element (5) connected to the drive (2) and aligned in a vertical path (Z-Z) as a result of gravitational force at least in a rest position;
a load-receiving device (7) which is connected to the load-bearing element (5); and
a regulating circuit for load-balancing purposes;

wherein the regulating circuit for load-balancing purposes comprises

a device (11) for generating a signal (S), which contains information relating to movement along the path covered during an initial course of a substantially vertical (Z-Z) movement of the load bearing element (5) out of the rest position under the action of the drive (2) and which serves as an input signal for controlling the drive (2) to balance the load in the vertical path (Z-Z);

a regulating member (12) operative in response to a deviation (ΔS) of the signal (S) from a desired value (W) to emit a regulating signal (R); and

an actuating member (13) for the drive (2), which receives the regulating signal (R) and is operative to control constant-switching of the drive (2), whereby the vertical (Z-Z) movement of the load bearing element (5) out of the rest position decreases to standstill, when the signal (S) and the desired value (W) correspond so that the deviation (ΔS) of the signal (S) from the desired value (W) is zero.

28. (Currently Amended) A system for controlling a load lifting apparatus (1), comprising

a controllable drive (2);

a load-bearing element (5) connected to the drive (2) and aligned at least in a vertical path (Z-Z) as a result of gravitational force in a rest position of the load-bearing element;

a load-receiving device (7) connected to the load-bearing element (5); and

a regulating circuit operatively associated with the controllable drive (2) for load-balancing purposes, the regulating circuit comprising:

a device (11) responsive to movement of the load-receiving device on the vertical path (Z-Z) for generating a signal (S) for balancing the load (9) in the vertical path without presetting the weight of the load;

the regulating circuit operating, after the load (9) is received by means of the load-receiving device (7), to automatically increase the torque of the

drive (2) until a substantially vertical (Z-Z) movement of the load bearing element (5) out of the rest position begins, thereby causing the device (11) to generate the signal (S),

which contains information dependent on and corresponding to a ~~path~~ an incremental course of movement covered during the beginning of the substantially vertical (Z-Z) movement of the load bearing element (5), and

which provides an input signal for controlling the drive (2) so as to balance the load in the vertical path (Z-Z); and

the regulating circuit operating to constant-switch the drive (2) in response to a zero deviation (ΔS) of said signal (S) from a predetermined value (W), so as to maintain the load-receiving device (7) and the load balanced in the substantially vertical path.

29. (Currently Amended) A system for controlling a load lifting apparatus (1), comprising

a controllable drive (2);

a load-bearing element (5) connected to the drive (2) and aligned at least in a vertical path Z-Z) as a result of gravitational force in a rest position of the load-bearing element;

a load-receiving device (7) connected to the load-bearing element (5); and

a regulating circuit operatively associated with the controllable drive (2) for load-balancing purposes;

the regulating circuit comprising a device (11) for generating a signal (S)

said device (11) being an incremental encoder which is arranged co-

axially with a drum (6) or with a drive shaft of the drive (2) and

said signal (S) corresponding to an angle of rotation of the drum

(6) or the drive shaft,

whereby to balance the load (9) in the vertical path (Z-Z) without the weight of the load being preset,

after the load (9) is received by means of the load-receiving device (7) the regulating circuit operates to automatically increase the torque of the drive (2) until a substantially vertical (Z-Z) movement of the load bearing element (5) out of the rest position begins, causing the device (11) to generate the signal (S)

which contains information dependent on and corresponding to a path an incremental course of movement covered during the beginning of the substantially vertical (Z-Z) movement of the load bearing element (5), and

which serves as an input signal for controlling the drive (2) to balance the load in the vertical path (Z-Z); and

the regulating circuit operating to constant-switch the drive (2) in response to a zero deviation (ΔS) of said signal (S) from a predetermined value

(W), so as to maintain the load-receiving device (7) and the load balanced in the substantially vertical path.

30. (Currently Amended) A system for controlling a load lifting apparatus (1), comprising

a controllable drive (2);

a load-bearing element (5) connected to the drive (2) and aligned in a vertical path (Z-Z) as a result of gravitational force at least in a rest position;

a load-receiving device (7) connected to the load-bearing element (5); and

a regulating circuit operatively associated with the controllable drive (2) for load-balancing purposes;

the regulating circuit comprising:

a device (11) for generating a signal (S)

which serves as an input signal for controlling the drive (2) and which contains information dependent on and relating to a an incremental movement ~~along the path covered~~ during an initial course of a substantially vertical (Z-Z) movement of the load bearing element (5), and

which serves as an input signal for controlling the drive (2) to balance the load in the vertical path (Z-Z),

so that, in response to a zero deviation (ΔS) of said signal (S) from a predetermined value (W), the drive (2) is constant-switched to balance the load with no vertical movement whereby the vertical (Z-Z) movement of the load bearing element (5) out of the rest position decreases to standstill; and

a controller for the substantially vertical (Z-Z) movement of the load bearing element (5), the controller comprising:

a handling device (10) for the load-receiving device;

a device (15) for generating a force-dependent signal (P) which corresponds to a manipulation force (F) acting substantially vertically (Z-Z) on the handling device (10);

a control member (14) which is operative in response to a deviation (ΔP) of the force-dependent signal (P) from a desired value (W) to emit a control signal (T) for the drive (2) for initiating and controlling the speed of the vertical (Z-Z) movement of the load bearing element (5), said movement corresponding to the direction and the magnitude of the manipulation force (F); and

a setting member (16) which is connected to the drive (2) or to an the actuating member (13) thereof and, operative in response to a signal (I, Q) corresponding to the load (9) or in response to the signal (S), changes the desired value (W), which determines the deviation (ΔP) of the force-dependent signal (P), or changes the transmission behavior of the setting member (16) so that the drive (2) brakes the vertical (Z-Z) movement of the load bearing element (5) ~~can be braked in dependence on~~ in response to the signal (S).